



## **Optimal Control of Compositional and Thermal Recovery Processes**

### **A C/C++ Simulator with Capabilities for Gradient Computations**

**Ritschel, Tobias K.S.; Jørgensen, John Bagterp**

*Publication date:*  
2017

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Ritschel, T. K. S., & Jørgensen, J. B. (2017). *Optimal Control of Compositional and Thermal Recovery Processes: A C/C++ Simulator with Capabilities for Gradient Computations*. Abstract from Danish Hydrocarbon Research and Technology Centre Technology Conference 2017, Lyngby, Denmark.

---

#### **General rights**

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

## Optimal Control of Compositional and Thermal Recovery Processes

### A C/C++ Simulator with Capabilities for Gradient Computations

*Tobias K. S. Ritschel and John Bagterp Jørgensen*

*Department of Applied Mathematics and Computer Science & Center for Energy Resources Engineering (CERE)  
Technical University of Denmark, DK-2800 Kgs. Lyngby, Denmark.*

We develop numerical algorithms for optimal control of oil and gas recovery. The algorithms combine simulations of the subsurface reservoir flow with a numerical optimization algorithm. The optimization algorithm iteratively improves the production strategy until an optimal strategy is reached.

The optimization requires a number of simulations, each of which is computationally expensive. We therefore use efficient optimization algorithms combined with an adjoint method to compute gradients, which requires significantly fewer simulations compared to simpler gradient-free optimization algorithms.

We present a numerical example of optimal control of compositional and thermal reservoir flow. The example is based on a recently developed C/C++ code, and the implementation uses a cubic equation of state to evaluate thermodynamic properties of the fluid.




Fig. 1: Diagram illustrating the role of optimal control (the blue loop) in a production optimization workflow (known as closed-loop reservoir management).